

A feature-rich printer offering more for less

Providing everything from a high paper capacity and Wi-Fi connection to duplex printing and compact design, the ECOSYS PA4000wx is a gem in our ECOSYS line. This printer is highly reliable due to long-life parts, with rapid print speeds and a low TCO.



ECOSYS PA4000wx



A4 monochrome printer

Up to 40 pages per minute

1200 x 1200 dpi resolution

Specifications

GENERAL

KYOCERA ECOSYS Laser Monochrome Multifunctional printer
Operation panel: LCD 21 characters, 5 lines
Type: Desktop
Engine speed:
Up to 40 A4 pages per minute simplex (single-sided),
Up to 20 A4 pages per minute duplex (both sides)
Resolution: 1200 x 1200 dpi (print)
Recommended Print Volume: Average 2,000 pages per month
Maximum Print Volume: 80,000 pages per month
Maximum Life: 200,000 pages or 5 years
Warm-up time: Approx. 15 seconds or less (after switching on)
Time to first print: Approx. 6.4 seconds or less
CPU: ARM Cortex-A53, 1.0GHz
Memory: Standard 512 MB
Standard interface: USB 2.0 (Hi-Speed), Network (10BASE-T/100BASE-TX/1000BASE-T), WLAN (802.11a/b/g/n/ac, Wi-Fi Direct, 2.4/5 GHz), USB host for USB flash memory, slot for optional SD/SDHC card
Integrated accounting: 20 department codes
Dimensions (W x D x H):
Without packaging: 375 x 393 x 272 mm,
387 x 393 x 272 mm (including a louver ensuring air flow) With packaging: 516 x 500 x 400 mm
Weight: Without packaging: Approx. 14.5 kg (with bundled toner), Approx. 14.0 kg (without bundled toner)
With packaging: 18 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
Printing: 555.9 W
Ready mode: 6.0 W
Sleep-mode: 0.3 W
Noise (sound pressure level: ISO 7779/ISO 9296):
Printing: 52 dB (A)
Quiet mode: 48 dB (A)
Stand-by: 29 dB (A)
Safety standards: TÜV/GS, CE
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: Multi-purpose tray: 100 sheets at 80 g/m², 60–220 g/m², A6, A5, A4, custom (70 x 148 – 216 x 356 mm).
Standard universal paper cassette: 250 sheets at 80 g/m², 60–163 g/m², A6, A5, A4, custom (105 x 148 – 216 x 356 mm).
Max. input capacity with options: 850 sheets at 80 g/m².
Duplex: Standard duplex unit, two-sided printing, 60–163 g/m², A5, A4, custom (140 x 210 – 216 x 356 mm).
Output capacity: Max. 250 sheets (face-down)

PRINT FUNCTIONS

Controller language: PRESCRIBE
Emulations: PCL 6 (5e, XL), KPDL3 (PostScript 3 compatible), Lineprinter, IBM Proprinter, Epson LQ-850, PDF Direct Print 1.7, 2.0, XPS/Open XPS Direct Print, TIFF Direct Print
Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 one-dimensional barcodes (e.g. EAN-8, EAN-13, EAN-128), as well as support for two-dimensional barcodes PDF417 under PRESCRIBE (PCL and other barcodes available an option)
Print features: "Proof and hold", Job storage¹, Quick copy¹, Private print¹, Data storage method with PIN code or password¹, Internet printing IPP 1.0, E-mail printing, WSD Print, EcoPrint - toner save mode, AirPrint, Mopria, Microsoft Universal Print, Job batch output, Image Refinement, Pull print, VPSX, IPP PIN Print, Kyocera Cloud Access, optional Kyocera Cloud Print and Scan selected function integration
Security features: Secure Boot, Run-time Integrity Check, Allowlisting, TLS 1.3, IPsec, HTTPS, SNMPv3, "Confidential printing" with PIN code request¹, encrypted PDF direct printing, Security Watermark, IPP over TLS, WSD, local and network authentication, Windows authentication (NTLM v2, Kerberos), Restriction of the user group through user login administration, IP filtering, port number restriction, blocking of interfaces, Security Quick Setup, SIEM Support (SysLog), SCEP, OCSP/CRL, Wi-Fi Certified WPA3, optional TPM (Trusted Platform Module)
Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Microsoft Universal Print, Wi-Fi Direct

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752
TK-1264 Toner Kit: Microfine toner black for 10,000 pages A4. Capacity of starter toner is 3,600 pages A4.

OPTIONS

PF-1100 Paper feeder (max. 2 units): Max. 250 sheets at 80 g/m², 60 – 163 g/m²; A6, A5, A4, custom (105 mm x 148 mm – 216mm x 356mm)

SECURITY

UG-33: ThinPrint support
UG-50: TPM (Trusted Platform Module), additional protection of confidential data
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

WARRANTY

2 years return-to-base as standard.

WHAT'S IN THE BOX:

Main unit, starter toner for 3,600 pages, Quick Guide, safety instructions and power supply cord.

¹Optional SD/SDHC memory card is required.

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.



KYOCERA Document Solutions Partner

JUL2024PA4000wx/VER1.0

Total Print Solutions

Unit 7, Nambawan Delite Center
Prince Philip Highway
Honiara

Email: sales@tps.com.sb

Tel: +677 27313

Web: www.tps.com.sb



TOTAL
PRINT SOLUTIONS

KYOCERA
Authorised Dealer

*KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free.
Specifications are subject to change without notice. Information is correct at time of going to press.
All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.